

LUXURY MINI MILLION 1

Revision nr.1 Dated 09/10/2018 Printed on 15/10/2018 Page n. 1 / 12

Safety Data Sheet

According to Annex II to REACH - Regulation 2015/830

SECTION 1. Identification of the substance/mixture and of the company/undertaking

1.1. Product identifier

Product name LUXURY PROFESSIONAL MILLION 1

1.2. Relevant identified uses of the substance or mixture and uses advised against

Intended use Profumatore

1.3. Details of the supplier of the safety data sheet

Name

Full address Profumi & Co s.r.l.c.r.
District and Country Via Bellelli, 1/c
42015 Correggio

ITALIA

(RE)

tel. 0425/405615 fax 0425/408308

e-mail address of the competent person responsible for the Safety Data Sheet

Ufficiotecnico@eurodet.it

Product distribution by: SIMONE ARTONI

1.4. Emergency telephone number

For urgent inquiries refer to CAV Ospedale Niguarda Milano 0266101029

SECTION 2. Hazards identification

2.1. Classification of the substance or mixture

The product is classified as hazardous pursuant to the provisions set forth in (EC) Regulation 1272/2008 (CLP) (and subsequent amendments and supplements). The product thus requires a safety datasheet that complies with the provisions of (EU) Regulation 2015/830. Any additional information concerning the risks for health and/or the environment are given in sections 11 and 12 of this sheet.

Hazard classification and indication:

Flammable liquid, category 3	H226	Flammable liquid and vapour.
Eye irritation, category 2	H319	Causes serious eye irritation.
Skin sensitization, category 1A	H317	May cause an allergic skin reaction.
Specific target organ toxicity - single exposure	H336	May cause drowsiness or dizziness.

category 3

Hazardous to the aquatic environment, chronic H412 Harmful to aquatic life with long lasting effects.

toxicity, category 3

2.2. Label elements

Hazard labelling pursuant to EC Regulation 1272/2008 (CLP) and subsequent amendments and supplements.

Hazard pictograms:





Signal words: Warning

Hazard statements:

H226
H319
Causes serious eye irritation.
H317
May cause an allergic skin reaction.
H336
May cause drowsiness or dizziness.
H412
Harmful to aquatic life with long lasting effects.



LUXURY MINI MILLION 1

Revision nr.1 Dated 09/10/2018 Printed on 15/10/2018 Page n. 2 / 12

SECTION 2. Hazards identification .../>>

EUH208 Contains: -METHYL-4-(2,6,6-TRIMETHYL-2-CYCLOHEXEN-1-YL)-3-BUTEN-2-ONE (MAIN

COMPONENT)

7-HYDROXY-3,7-DIMETHYLOCTAN-1-AL

AMAROCIT

ALPHA HEXYL CINNAMALDEHYDE

(R)-p-mentha-1,8-diene 1,2-BENZOPYRONE

CMR CAT. 3 2-METHYL-3(4-TERT-BUTYLPHENY) PROPANAL

May produce an allergic reaction.

Precautionary statements:

P501 Dispose of contents in accordance with local regulation.

P102 Keep out of reach of children.

P210 Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.

P280 Wear protective gloves/ protective clothing / eye protection / face protection.

P271 Use only outdoors or in a well-ventilated area.

P101 If medical advice is needed, have product container or label at hand.

Contains: OTNE (1-(1,2,3,4,5,6,7,8 Octahydro-2,3,8,8-tetramethyl-2-naphthalenyl) ethanone)

ALPHA HEXYL CINNAMALDEHYDE (ETHOXYMETHOXY)CYCLODODECANE

AMAROCIT

2.3. Other hazards

On the basis of available data, the product does not contain any PBT or vPvB in percentage greater than 0,1%.

SECTION 3. Composition/information on ingredients

3.1. Substances

Information not relevant

3.2. Mixtures

Contains:

Identification x = Conc. % Classification 1272/2008 (CLP)

ETHANOL

CAS 64-17-5 $30 \le x < 50$ Flam. Liq. 2 H225

EC 200-578-6 INDEX 603-002-00-5

Reg. no. 01-2119457610-43-xxxx

PROPAN-2-OL

CAS 67-63-0 10 ≤ x < 20 Flam. Liq. 2 H225, Eye Irrit. 2 H319, STOT SE 3 H336

EC 200-661-7 INDEX 603-117-00-0

Reg. no. 01-2119457558-25-xxxx

OTNE (1-(1,2,3,4,5,6,7,8 Octahydro-2,3,8,8-tetramethyl-2-naphthalenyl) ethanone)

CAS 54464-57-2 1 ≤ x < 2,5 Skin Irrit. 2 H315, Skin Sens. 1 H317, Aquatic Chronic 2 H411

EC INDEX

(ETHOXYMETHOXY)CYCLODODECANE

CAS 58567-11-6 0,1 ≤ x < 0,5 Skin Irrit. 2 H315, Skin Sens. 1A H317, Aquatic Chronic 2 H411

EC 261-332-1

INDEX

Reg. no. 01-2119971571-34

CMR CAT. 3 2-METHYL-3(4-TERT-BUTYLPHENY) PROPANAL

CAS 80-54-6 $0 \le x < 0.5$ Repr. 2 H361f, Acute Tox. 4 H302, Skin Irrit. 2 H315, Skin Sens. 1 H317,

Aquatic Chronic 2 H411

EC 201-289-8

INDEX



LUXURY MINI MILLION 1

Revision nr.1 Dated 09/10/2018 Printed on 15/10/2018 Page n. 3 / 12

SECTION 3. Composition/information on ingredients .../>>

1,2-BENZOPYRONE

CAS 91-64-5 $0 \le x < 0.5$ Acute Tox. 4 H302, Skin Sens. 1B H317

EC 202-086-7

INDEX

Reg. no. 01-2119943756-26

Galaxolide

CAS 1222-05-5 $0.25 \le x < 0.5$ Aquatic Acute 1 H400 M=1, Aquatic Chronic 1 H410 M=1

EC 214-946-9 INDEX 603-212-00-7

7-ACETYL-1,1,3,4,4,6-HEXAMETHYL TETRALIN

CAS 21145-77-7 0 ≤ x < 0.25 Acute Tox. 4 H302, Aquatic Acute 1 H400 M=1, Aquatic Chronic 1 H410 M=1

EC 244-240-6

INDEX

(R)-p-mentha-1,8-diene

CAS 5989-27-5 0 ≤ x < 0,25 Flam. Liq. 3 H226, Skin Irrit. 2 H315, Skin Sens. 1 H317, Aquatic Acute 1 H400 M=1,

Aquatic Chronic 1 H410 M=1,

Classification note according to Annex VI to the CLP Regulation: C

EC 227-813-5 INDEX 601-029-00-7

ALPHA HEXYL CINNAMALDEHYDE

CAS 101-86-0 0,1 ≤ x < 0,25 Skin Sens. 1A H317, Aquatic Acute 1 H400 M=1, Aquatic Chronic 1 H410 M=1

EC 202-983-3

INDEX
AMAROCIT

CAS 67674-46-8 0,1 ≤ x < 0,5 Skin Irrit. 2 H315, Skin Sens. 1A H317, Aquatic Chronic 3 H412

EC 266-885-2

INDEX

7-HYDROXY-3,7-DIMETHYLOCTAN-1-AL

CAS 107-75-5 $0 \le x < 0.5$ Eye Irrit. 2 H319, Skin Sens. 1 H317

EC 203-518-7

INDEX

-METHYL-4-(2,6,6-TRIMETHYL-2-CYCLOHEXEN-1-YL)-3-BUTEN-2-ONE (MAIN COMPONENT)

CAS 127-51-5 $0 \le x < 0,5$ Skin Sens. 1 H317, Aquatic Chronic 2 H411

EC 215-635-0

INDEX
TOLUENE

CAS 108-88-3 0 ≤ x < 0,5 Flam. Liq. 2 H225, Repr. 2 H361d, Asp. Tox. 1 H304, STOT RE 2 H373, Skin Irrit. 2 H315

, STOT SE 3 H336

EC 203-625-9 INDEX 601-021-00-3

The full wording of hazard (H) phrases is given in section 16 of the sheet.

SECTION 4. First aid measures

4.1. Description of first aid measures

EYES: Remove contact lenses, if present. Wash immediately with plenty of water for at least 15 minutes, opening the eyelids fully. If problem persists, seek medical advice.

SKIN: Remove contaminated clothing. Rinse skin with a shower immediately. Get medical advice/attention immediately. Wash contaminated clothing before using it again.

INHALATION: Remove to open air. If the subject stops breathing, administer artificial respiration. Get medical advice/attention immediately.

INGESTION: Get medical advice/attention immediately. Do not induce vomiting. Do not administer anything not explicitly authorised by a doctor.

4.2. Most important symptoms and effects, both acute and delayed

Specific information on symptoms and effects caused by the product are unknown.

4.3. Indication of any immediate medical attention and special treatment needed

Information not available

SECTION 5. Firefighting measures

5.1. Extinguishing media

SUITABLE EXTINGUISHING EQUIPMENT

Extinguishing substances are: carbon dioxide, foam, chemical powder. For product loss or leakage that has not caught fire, water spray can



LUXURY MINI MILLION 1

Revision nr.1 Dated 09/10/2018 Printed on 15/10/2018 Page n. 4 / 12

SECTION 5. Firefighting measures .../>>

be used to disperse flammable vapours and protect those trying to stem the leak.UNSUITABLE EXTINGUISHING EQUIPMENT Do not use jets of water. Water is not effective for putting out fires but can be used to cool containers exposed to flames to prevent explosions.

5.2. Special hazards arising from the substance or mixture

HAZARDS CAUSED BY EXPOSURE IN THE EVENT OF FIRE

Excess pressure may form in containers exposed to fire at a risk of explosion. Do not breathe combustion products.

5.3. Advice for firefighters

GENERAL INFORMATION

Use jets of water to cool the containers to prevent product decomposition and the development of substances potentially hazardous for health. Always wear full fire prevention gear. Collect extinguishing water to prevent it from draining into the sewer system. Dispose of contaminated water used for extinction and the remains of the fire according to applicable regulations.

SPECIAL PROTECTIVE EQUIPMENT FOR FIRE-FIGHTERS

Normal fire fighting clothing i.e. fire kit (BS EN 469), gloves (BS EN 659) and boots (HO specification A29 and A30) in combination with self-contained open circuit positive pressure compressed air breathing apparatus (BS EN 137).

SECTION 6. Accidental release measures

6.1. Personal precautions, protective equipment and emergency procedures

Block the leakage if there is no hazard.

Wear suitable protective equipment (including personal protective equipment referred to under Section 8 of the safety data sheet) to prevent any contamination of skin, eyes and personal clothing. These indications apply for both processing staff and those involved in emergency procedures.

Send away individuals who are not suitably equipped. Use explosion-proof equipment. Eliminate all sources of ignition (cigarettes, flames, sparks, etc.) from the leakage site.

6.2. Environmental precautions

The product must not penetrate into the sewer system or come into contact with surface water or ground water.

6.3. Methods and material for containment and cleaning up

Collect the leaked product into a suitable container. Evaluate the compatibility of the container to be used, by checking section 10. Absorb the remainder with inert absorbent material.

Make sure the leakage site is well aired. Contaminated material should be disposed of in compliance with the provisions set forth in point 13.

6.4. Reference to other sections

Any information on personal protection and disposal is given in sections 8 and 13.

SECTION 7. Handling and storage

7.1. Precautions for safe handling

Keep away from heat, sparks and naked flames; do not smoke or use matches or lighters. Vapours may catch fire and an explosion may occur; vapour accumulation is therefore to be avoided by leaving windows and doors open and ensuring good cross ventilation. Without adequate ventilation, vapours may accumulate at ground level and, if ignited, catch fire even at a distance, with the danger of backfire. Avoid bunching of electrostatic charges. When performing transfer operations involving large containers, connect to an earthing system and wear antistatic footwear. Vigorous stirring and flow through the tubes and equipment may cause the formation and accumulation of electrostatic charges. In order to avoid the risk of fires and explosions, never use compressed air when handling. Open containers with caution as they may be pressurised. Do not eat, drink or smoke during use. Avoid leakage of the product into the environment.

7.2. Conditions for safe storage, including any incompatibilities

Store only in the original container. Store the containers sealed, in a well ventilated place, away from direct sunlight. Store in a well ventilated place, keep far away from sources of heat, naked flames and sparks and other sources of ignition. Keep containers away from any incompatible materials, see section 10 for details.

7.3. Specific end use(s)

Information not available



LUXURY MINI MILLION 1

Revision nr.1 Dated 09/10/2018 Printed on 15/10/2018 Page n. 5 / 12

SECTION 8. Exposure controls/personal protection

8.1. Control parameters

Regulatory References:

DEU Deutschland TRGS 900 (Fassung 31.1.2018 ber.) - Liste der Arbeitsplatzgrenzwerte und Kurzzeitwerte

FRA France JORF n°0109 du 10 mai 2012 page 8773 texte n° 102

GBR United Kingdom EH40/2005 Workplace exposure limits ITA Italia Decreto Legislativo 9 Aprile 2008, n.81

PRT Portugal Ministério da Economia e do Emprego Consolida as prescrições mínimas em matéria de protecção

dos trabalhadores contra os riscos para a segurança e a saúde devido à exposição a agentes

químicos no trabalho - Diaro da Republica I 26; 2012-02-06

ROU România Monitorul Oficial al României 44; 2012-01-19

EU OEL EU Directive (EU) 2017/2398; Directive (EU) 2017/164; Directive 2009/161/EU; Directive 2006/15/EC;

Directive 2004/37/EC; Directive 2000/39/EC; Directive 91/322/EEC.

TLV-ACGIH ACGIH 2018

ETHANOL										
Threshold Limit Value										
Type	Country	TWA/8h		STEL/15r	min					
		mg/m3	ppm	mg/m3	ppm					
AGW	DEU	960	500	1920	1000					
MAK	DEU	960	500	1920	1000					
VLEP	FRA	1900	1000	9500	5000					
WEL	GBR	1920	1000							
TLV	ROU	1900	1000	9500	5000					
TLV-ACGIH				1884	1000					

PROPAN-2-OL									
Threshold Limit Value									
Type	Country	TWA/8h		STEL/15r	min				
		mg/m3	ppm	mg/m3	ppm				
AGW	DEU	500	200	1000	400				
MAK	DEU	500	200	1000	400				
VLEP	FRA			980	400				
WEL	GBR	999	400	1250	500				
TLV	ROU	200	81	500	203	SKIN			
TLV-ACGIH		492	200	983	400				

				то	LUENE			
Threshold Limit	Value							
Туре	Country	TWA/8h		STEL/15	STEL/15min			
		mg/m3	ppm	mg/m3	ppm			
AGW	DEU	190	50	760	200	SKIN		
MAK	DEU	190	50	760	200			
VLEP	FRA	76,8	20	384	100	SKIN		
WEL	GBR	191	50	384	100	SKIN		
VLEP	ITA	192	50			SKIN		
VLE	PRT	192	50	384	100	SKIN		
TLV	ROU	192	50	384	100	SKIN		
OEL	EU	192	50	384	100	SKIN		
TLV-ACGIH		75,4	20					

Legend

(C) = CEILING; INHAL = Inhalable Fraction; RESP = Respirable Fraction; THORA = Thoracic Fraction.

8.2. Exposure controls

As the use of adequate technical equipment must always take priority over personal protective equipment, make sure that the workplace is well aired through effective local aspiration.

When choosing personal protective equipment, ask your chemical substance supplier for advice.

Personal protective equipment must be CE marked, showing that it complies with applicable standards.

Provide an emergency shower with face and eye wash station.

HAND PROTECTION

Protect hands with category III work gloves (see standard EN 374).



LUXURY MINI MILLION 1

Revision nr.1 Dated 09/10/2018 Printed on 15/10/2018 Page n. 6 / 12

SECTION 8. Exposure controls/personal protection .../>>

The following should be considered when choosing work glove material: compatibility, degradation, failure time and permeability. The work gloves' resistance to chemical agents should be checked before use, as it can be unpredictable. The gloves' wear time depends on the duration and type of use.

SKIN PROTECTION

Wear category II professional long-sleeved overalls and safety footwear (see Directive 89/686/EEC and standard EN ISO 20344). Wash body with soap and water after removing protective clothing.

Consider the appropriateness of providing antistatic clothing in the case of working environments in which there is a risk of explosion. EYE PROTECTION

Wear airtight protective goggles (see standard EN 166).

RESPIRATORY PROTECTION

If the threshold value (e.g. TLV-TWA) is exceeded for the substance or one of the substances present in the product, wear a mask with a type AX filter, whose limit of use will be defined by the manufacturer (see standard EN 14387). In the presence of gases or vapours of various kinds and/or gases or vapours containing particulate (aerosol sprays, fumes, mists, etc.) combined filters are required.

Respiratory protection devices must be used if the technical measures adopted are not suitable for restricting the worker's exposure to the threshold values considered. The protection provided by masks is in any case limited.

If the substance considered is odourless or its olfactory threshold is higher than the corresponding TLV-TWA and in the case of an emergency, wear open-circuit compressed air breathing apparatus (in compliance with standard EN 137) or external air-intake breathing apparatus (in compliance with standard EN 138). For a correct choice of respiratory protection device, see standard EN 529. ENVIRONMENTAL EXPOSURE CONTROLS

The emissions generated by manufacturing processes, including those generated by ventilation equipment, should be checked to ensure compliance with environmental standards.

Product residues must not be indiscriminately disposed of with waste water or by dumping in waterways.

liquid

SECTION 9. Physical and chemical properties

9.1. Information on basic physical and chemical properties

Colour orange characteristic Odour Odour threshold Not available рΗ 7 Melting point / freezing point 0 °C Initial boiling point 60 °C Boiling range Not available Flash point 55 °C **Evaporation Rate** Not available Flammability of solids and gases flammable gas Lower inflammability limit Not available Upper inflammability limit Not available Lower explosive limit Not available Not available Upper explosive limit Vapour pressure Not available Vapour density Not available Relative density 0.92 Solubility soluble Not available Partition coefficient: n-octanol/water Auto-ignition temperature Not available Decomposition temperature Not available Not available Viscosity Explosive properties Not available Not available Oxidising properties

9.2. Other information

Appearance

Information not available

SECTION 10. Stability and reactivity

10.1. Reactivity

There are no particular risks of reaction with other substances in normal conditions of use.

TOLUENE

Avoid exposure to: light.



LUXURY MINI MILLION 1

Revision nr.1 Dated 09/10/2018 Printed on 15/10/2018 Page n. 7 / 12

SECTION 10. Stability and reactivity .../>>

10.2. Chemical stability

The product is stable in normal conditions of use and storage.

10.3. Possibility of hazardous reactions

The vapours may also form explosive mixtures with the air.

ETHANOI

Risk of explosion on contact with: alkaline metals,alkaline oxides,calcium hypochlorite,sulphur monofluoride,acetic anhydride,acids,concentrated hydrogen peroxide,perchlorates,perchloric acid,perchloronitrile,mercury nitrate,nitric acid,silver,silver nitrate,ammonia,silver oxide,ammonia,strong oxidising agents,nitrogen dioxide.May react dangerously with: bromoacetylene,chlorine acetylene,bromine trifluoride,chromium trioxide,chromyl chloride,fluorine,potassium tert-butoxide,lithium hydride,phosphorus trioxide,black platinum,zirconium (IV) chloride,zirconium (IV) iodide.Forms explosive mixtures with: air.

TOLLIENE

Risk of explosion on contact with: fuming sulphuric acid,nitric acid,silver perchlorate,nitrogen dioxide,non-metal halogenates,acetic acid,organic nitrocompounds. May form explosive mixtures with: air. May react dangerously with: strong oxidising agents, strong acids, sulphur.

10.4. Conditions to avoid

Avoid overheating. Avoid bunching of electrostatic charges. Avoid all sources of ignition.

FTHANOI

Avoid exposure to: sources of heat,naked flames.

10.5. Incompatible materials

Information not available

10.6. Hazardous decomposition products

In the event of thermal decomposition or fire, gases and vapours that are potentially dangerous to health may be released.

SECTION 11. Toxicological information

In the absence of experimental data for the product itself, health hazards are evaluated according to the properties of the substances it contains, using the criteria specified in the applicable regulation for classification.

It is therefore necessary to take into account the concentration of the individual hazardous substances indicated in section 3, to evaluate the toxicological effects of exposure to the product.

11.1. Information on toxicological effects

Metabolism, toxicokinetics, mechanism of action and other information

Information not available

Information on likely routes of exposure

TOLUENE

WORKERS: inhalation; contact with the skin.

POPULATION: ingestion of contaminated food or water; inhalation of ambient air; contact with the skin of products containing the substance

Delayed and immediate effects as well as chronic effects from short and long-term exposure

TOLUENE

Toxic effect on the central and peripheral nervous system with encephalopathy and polyneuritis; irritating for the skin, conjunctiva, cornea and respiratory apparatus.

Interactive effects

TOLUENE

Certain drugs and other industrial products can interfere with the metabolism of the toluene.

ACUTE TOXICITY

LC50 (Inhalation) of the mixture: LD50 (Oral) of the mixture:

Not classified (no significant component)



LUXURY MINI MILLION 1

Revision nr.1 Dated 09/10/2018 Printed on 15/10/2018 Page n. 8 / 12

SECTION 11. Toxicological information .../>>

LD50 (Dermal) of the mixture:

Not classified (no significant component) Not classified (no significant component)

TOLUENE

 LD50 (Oral)
 5580 mg/kg Rat

 LD50 (Dermal)
 12124 mg/kg Rabbit

 LC50 (Inhalation)
 28,1 mg/l/4h Rat

ETHANOL

LD50 (Oral) > 5000 mg/kg Rat

LC50 (Inhalation) 120 mg/l/4h Pimephales promelas

PROPAN-2-OL

 LD50 (Oral)
 4710 mg/kg Rat

 LD50 (Dermal)
 12800 mg/kg Rat

 LC50 (Inhalation)
 72,6 mg/l/4h Rat

SKIN CORROSION / IRRITATION

Does not meet the classification criteria for this hazard class

SERIOUS EYE DAMAGE / IRRITATION

Causes serious eye irritation

RESPIRATORY OR SKIN SENSITISATION

Sensitising for the skin

May produce an allergic reaction.

Contains:

-METHYL-4-(2,6,6-TRIMETHYL-2-CYCLOHEXEN-1-YL)-3-BUTEN-2-ONE (MAIN COMPONENT)

7-HYDROXY-3,7-DIMETHYLOCTAN-1-AL

AMAROCIT

ALPHA HEXYL CINNAMALDEHYDE

(R)-p-mentha-1,8-diene

1,2-BENZOPYRONE

CMR CAT. 3 2-METHYL-3(4-TERT-BUTYLPHENY) PROPANAL

GERM CELL MUTAGENICITY

Does not meet the classification criteria for this hazard class

CARCINOGENICITY

Does not meet the classification criteria for this hazard class

TOLUENE

Classified in Group 3 (not classifiable as a human carcinogen) by the International Agency for Research on Cancer (IARC) - (IARC, 1999).

The US Environmental Protection Agency (EPA) affirms that "the data is inadequate for an assessment of the carcinogenic potential".

REPRODUCTIVE TOXICITY

Does not meet the classification criteria for this hazard class

STOT - SINGLE EXPOSURE

May cause drowsiness or dizziness

STOT - REPEATED EXPOSURE

Does not meet the classification criteria for this hazard class

ASPIRATION HAZARD

Does not meet the classification criteria for this hazard class

LUXURY MINI MILLION 1

Revision nr.1 Dated 09/10/2018 Printed on 15/10/2018 Page n. 9 / 12

SECTION 12. Ecological information

This product is dangerous for the environment and the aquatic organisms. In the long term, it have negative effects on aquatic environment.

12.1. Toxicity

Information not available

12.2. Persistence and degradability

TOLUENE

Solubility in water 100 - 1000 mg/l

Rapidly degradable

ETHANOL

Solubility in water 1000 - 10000 mg/l

Rapidly degradable

PROPAN-2-OL Rapidly degradable

12.3. Bioaccumulative potential

TOLUENE

Partition coefficient: n-octanol/water 2,73 BCF 90

ETHANOL

Partition coefficient: n-octanol/water -0,35

PROPAN-2-OL

Partition coefficient: n-octanol/water 0,05

12.4. Mobility in soil

Information not available

12.5. Results of PBT and vPvB assessment

On the basis of available data, the product does not contain any PBT or vPvB in percentage greater than 0,1%.

12.6. Other adverse effects

Information not available

SECTION 13. Disposal considerations

13.1. Waste treatment methods

Reuse, when possible. Product residues should be considered special hazardous waste. The hazard level of waste containing this product should be evaluated according to applicable regulations.

Disposal must be performed through an authorised waste management firm, in compliance with national and local regulations.

Waste transportation may be subject to ADR restrictions.

CONTAMINATED PACKAGING

Contaminated packaging must be recovered or disposed of in compliance with national waste management regulations.

SECTION 14. Transport information

14.1. UN number

ADR / RID, IMDG, IATA: 1987



LUXURY MINI MILLION 1

Revision nr.1 Dated 09/10/2018 Printed on 15/10/2018 Page n. 10 / 12

SECTION 14. Transport information .../>>

14.2. UN proper shipping name

ADR / RID: ALCOHOLS, N.O.S. (ETHANOL; PROPAN-2-OL) IMDG: ALCOHOLS, N.O.S. (ETHANOL; PROPAN-2-OL) IATA: ALCOHOLS, N.O.S. (ETHANOL; PROPAN-2-OL)

14.3. Transport hazard class(es)

ADR / RID: Class: 3 Label: 3

IMDG: Class: 3 Label: 3

IATA: Class: 3 Label: 3



14.4. Packing group

ADR / RID, IMDG, IATA: Ш

14.5. Environmental hazards

ADR / RID: NO IMDG: NO NO IATA:

14.6. Special precautions for user

Limited Quantities: 5 L ADR / RID: HIN - Kemler: 30 Tunnel restriction code: (D/E)

Special Provision: -IMDG: EMS: F-E, S-D Limited Quantities: 5 L

IATA: Cargo: Maximum quantity: 220 L Packaging instructions: 366 Packaging instructions: 355

Pass.: Maximum quantity: 60 L

A3, A180 Special Instructions:

14.7. Transport in bulk according to Annex II of Marpol and the IBC Code

Information not relevant

SECTION 15. Regulatory information

15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture

Seveso Category - Directive 2012/18/EC: P5c

Restrictions relating to the product or contained substances pursuant to Annex XVII to EC Regulation 1907/2006

Product

3 - 40 Point

Contained substance

Point 48 **TOLUENE**

Substances in Candidate List (Art. 59 REACH)

On the basis of available data, the product does not contain any SVHC in percentage greater than 0,1%.

Substances subject to authorisation (Annex XIV REACH)

None

Substances subject to exportation reporting pursuant to (EC) Reg. 649/2012:

Substances subject to the Rotterdam Convention:

None

Substances subject to the Stockholm Convention:

ΕN



PROFUMI & CO

LUXURY MINI MILLION 1

Revision nr.1 Dated 09/10/2018 Printed on 15/10/2018 Page n. 11 / 12

SECTION 15. Regulatory information .../>>

None

Healthcare controls

Workers exposed to this chemical agent must not undergo health checks, provided that available risk-assessment data prove that the risks related to the workers' health and safety are modest and that the 98/24/EC directive is respected.

15.2. Chemical safety assessment

No chemical safety assessment has been processed for the mixture and the substances it contains.

SECTION 16. Other information

Text of hazard (H) indications mentioned in section 2-3 of the sheet:

Flam. Liq. 2 Flammable liquid, category 2
Flam. Liq. 3 Flammable liquid, category 3
Repr. 2 Reproductive toxicity, category 2
Acute Tox. 4 Asp. Tox. 1 Aspiration hazard, category 1

STOT RE 2 Specific target organ toxicity - repeated exposure, category 2

Eye Irrit. 2 Eye irritation, category 2
Skin Irrit. 2 Skin irritation, category 2
Skin Sens. 1 Skin sensitization, category 1
Skin Sens. 1A Skin sensitization, category 1A
Skin Sens. 1B Skin sensitization, category 1B

STOT SE 3

Aquatic Acute 1

Aquatic Chronic 1

Aquatic Chronic 2

Aquatic Chronic 3

Aquatic Chronic 3

Specific target organ toxicity - single exposure, category 3

Hazardous to the aquatic environment, acute toxicity, category 1

Hazardous to the aquatic environment, chronic toxicity, category 2

Aquatic Chronic 3

Hazardous to the aquatic environment, chronic toxicity, category 3

H225 Highly flammable liquid and vapour.
 H226 Flammable liquid and vapour.
 H361d Suspected of damaging the unborn child.

H361f Suspected of damaging fertility.

H302 Harmful if swallowed.

H304 May be fatal if swallowed and enters airways.

H373 May cause damage to organs through prolonged or repeated exposure.

H319 Causes serious eye irritation.
H315 Causes skin irritation.

H317 May cause an allergic skin reaction.H336 May cause drowsiness or dizziness.

H400 Very toxic to aquatic life.

H410 Very toxic to aquatic life with long lasting effects.
 H411 Toxic to aquatic life with long lasting effects.
 H412 Harmful to aquatic life with long lasting effects.

LEGEND:

- ADR: European Agreement concerning the carriage of Dangerous goods by Road
- CAS NUMBER: Chemical Abstract Service Number
- CE50: Effective concentration (required to induce a 50% effect)
- CE NUMBER: Identifier in ESIS (European archive of existing substances)
- CLP: EC Regulation 1272/2008
- DNEL: Derived No Effect Level
- EmS: Emergency Schedule
- GHS: Globally Harmonized System of classification and labeling of chemicals
- IATA DGR: International Air Transport Association Dangerous Goods Regulation
- IC50: Immobilization Concentration 50%
- IMDG: International Maritime Code for dangerous goods
- IMO: International Maritime Organization
- INDEX NUMBER: Identifier in Annex VI of CLP
- LC50: Lethal Concentration 50%
- LD50: Lethal dose 50%
- OEL: Occupational Exposure Level
- PBT: Persistent bioaccumulative and toxic as REACH Regulation
- PEC: Predicted environmental Concentration
- PEL: Predicted exposure level
- PNEC: Predicted no effect concentration
- REACH: EC Regulation 1907/2006



LUXURY MINI MILLION 1

Revision nr.1 Dated 09/10/2018 Printed on 15/10/2018 Page n. 12 / 12

SECTION 16. Other information .../>>

- RID: Regulation concerning the international transport of dangerous goods by train- TLV: Threshold Limit Value
- TLV CEILING: Concentration that should not be exceeded during any time of occupational exposure.
- TWA STEL: Short-term exposure limit
- TWA: Time-weighted average exposure limit
- VOC: Volatile organic Compounds
- vPvB: Very Persistent and very Bioaccumulative as for REACH Regulation
- WGK: Water hazard classes (German).

GENERAL BIBLIOGRAPHY

- 1. Regulation (EC) 1907/2006 (REACH) of the European Parliament
- 2. Regulation (EC) 1272/2008 (CLP) of the European Parliament
- 3. Regulation (EU) 790/2009 (I Atp. CLP) of the European Parliament
- 4. Regulation (EU) 2015/830 of the European Parliament
- 5. Regulation (EU) 286/2011 (II Atp. CLP) of the European Parliament
- 6. Regulation (EU) 618/2012 (III Atp. CLP) of the European Parliament
- 7. Regulation (EU) 487/2013 (IV Atp. CLP) of the European Parliament
- 8. Regulation (EU) 944/2013 (V Atp. CLP) of the European Parliament
- 9. Regulation (EU) 605/2014 (VI Atp. CLP) of the European Parliament
- 10. Regulation (EU) 2015/1221 (VII Atp. CLP) of the European Parliament
- 11. Regulation (EU) 2016/918 (VIII Atp. CLP) of the European Parliament
- 12. Regulation (EU) 2016/1179 (IX Atp. CLP)
- 13. Regulation (EU) 2017/776 (X Atp. CLP)
- The Merck Index. 10th Edition
- Handling Chemical Safety
- INRS Fiche Toxicologique (toxicological sheet)
- Patty Industrial Hygiene and Toxicology
- N.I. Sax Dangerous properties of Industrial Materials-7, 1989 Edition
- IFA GESTIS website
- ECHA website
- Database of SDS models for chemicals Ministry of Health and ISS (Istituto Superiore di Sanità) Italy

Note for users:

The information contained in the present sheet are based on our own knowledge on the date of the last version. Users must verify the suitability and thoroughness of provided information according to each specific use of the product.

This document must not be regarded as a guarantee on any specific product property.

The use of this product is not subject to our direct control; therefore, users must, under their own responsibility, comply with the current health and safety laws and regulations. The producer is relieved from any liability arising from improper uses.

Provide appointed staff with adequate training on how to use chemical products.